

■表の見方

圧着・圧縮対象の端子及びコネクタの種類・サイズより、該当する機種を選定する例

		油圧ヘッド分離式	充電式					手動式					
		12号A	EP-520C	EP-1000A	REC-200M2H	REC-L1200M	S7G-M200R	REC-L1250M	S7G-M250R	REC-L1325M	REC-14A	REC-150F	1520FH
		234028	234030	234029	234039	234034	234036	234024	234017	234035	234037		
● : 本体付属 ○ : 別途手配													
裸圧着端子、棒型圧着端子、裸圧着スリーブ、圧着銅管端子													
AWG	mm ²												
16-14	2.0									●			
12-10	5.5									●			
8	8	○							○	●			
6	14	○			●	●	●	●	○	●	●		

裸圧着端子 8mm²を圧着する機種を選定する場合

圧着端子サイズ“8mm²”に○及び●記載がある機種・・・ 12号A(油圧ヘッド分離式)、REC-Li325M(充電式)、REC-14A(充電式)

該当機種の表示記載について

●は該当サイズのダイスが工具本体の標準付属品です。○は該当サイズのダイスが本体に付属されておらず、ダイスのレンタルを別途お申込みいただく商品です。

油圧ヘッド分離式	充電式	手動式
----------	-----	-----

		12号A	EP-520C	EP-1000A	REC-200M2H	REC-L1200M	S7G-M200R	S7G-M250R	REC-L1325M	S7G-M325R	REC-14A	REC-150F	REC-1520FH	REC-L1200	REC-325CH	REC-Li325	REC-Li15	REC-365CH	REC-Li16	EP-365	
		234028	234030	234029	234039	234034	234024	234017	233996	234035	234037	234038	234033	234031	234032	234022	234040				
● : 本体付属 ○ : 別途手配																					
裸圧着端子、棒型圧着端子、裸圧着スリーブ、圧着銅管端子																					
AWG	mm ²																				
16-14	2.0									●											
12-10	5.5									●											
8	8	○						○	○	●							○				
6	14	○			●	●	●	●	○	○	●	●	●	○	○	○	○	○	○	○	
4	22	○			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
2	38	○			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
1/0	60	●			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
2/0	70	○			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
3/0	80	●			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
4/0	100	●			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
250-300 MCM	150	●			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
300-350 MCM	180	●			●								●		●	●					
400 MCM	200	●			●	●	●	●	○	○		●	●	○	○	○	○	○	○	○	
	250	●						●	●	●											
500-600 MCM	325	●							●	●					●	●					

油圧ヘッド分離式	充電式	手動式
----------	-----	-----

●: 本体付属 ○: 別途手配	12号A	EP-520C	EP-1000A	REC-200M2H	REC-LI200M	REC-LI250M	S7G-M200R	S7G-M250R	REC-LI325M	S7G-M325R	REC-144A	REC-150F	REC-1520FH	REC-LI200	REC-325CH	REC-LI325	REC-LI15	REC-LI16	REC-LI16	EP-365
	234028	234030	234029	234039	234034	234036	234024	234017	233996	234035	234037	234038	234033	234031	234032	234022	234040			
T形コネクタ コネクタ品番																				
適用電線合計断面積																				
T-11	7.5~11			○	○	○	○	○	○	○							○	○	○	○
T-16	11.5~16			○	○	○	○	○	○	○							○	○	○	○
T-20	14~20			○	○	○	○	○	○	○							●	○	○	○
T-26	21~26			○	○	○	○	○	○	○							●	○	○	○
T-44	27~44			○	○	○	○	○	○	○							●	○	○	○
T-60	45~60			○	○	○	○	○	○	○							●	○	○	○
T-76	61~76			○	○	○	○	○	○	○							●	○	○	○
T-98	77~98			○	○	○	○	○	○	○							●	○	○	○
T-122	99~122	○		○	○	○	○	○	○	○							●	○	○	○
T-154	123~154	○		○														○	○	○
T-190	155~190	○		○														○	○	○
T-240	191~240	○		○														○	○	○
T-288	241~288	○																○	○	○
T-365	289~365	○																○	○	○
T-450	366~450	○																		
T-560	451~560	○																		
T-700	561~700	○																		
圧縮端子、圧縮スリーブ銅線用																				
8~14-12		○	○	○	○	○	○	○	○	○								○	○	○
22~38-14		○	○	○	○	○	○	○	○	○								○	○	○
45~70-19		○	○	○	○	○	○	○	○	○								○	○	○
38-60-22				○														○	○	○
75~100-23		○	○	○	○	○	○	○	○	○								○	○	○
110~125-26		○	○	○														○	○	○
150-29		○	○	○														○	○	○
180~200-32		○	○	○														○	○	
240-36		○	○																	
250-38		○	○																	
325-42		○	○																	
400~500-47		○	○																	
600-51			○																	
725~850-56			○																	
1000-64			○																	